

BP RLAT EVO

BETONEIRA PROFISSIONAL REBOCÁVEL
HORMIGONERA PROFESIONAL REMOLCABLE
BÉTONNIÈRE PROFESSIONNELLE TRACTABLE
PROFI ANHÄNGBARER BETONMISCHER
PROFESSIONAL TOWABLE CEMENT MIXER

Cremalheira e carreto em ferro fundido

Corona y piñon en hierro fundido

Couronne et pignon en fonte

Zahnkranz aus Gußeisen

Cast iron gear ring

Desmultiplicação em ferro nodular

Desmultiplicación en hierro nodular

Démultiplication en fonte nodulaire

Zahnrad aus Gußeisen

Nodular demultiplication




ESTRUTURA, BALDE E BOCA REFORÇADOS
ESTRUCTURA, CUBO Y BOCA REFORZADOS
BOMBO CON 3 PALAS MEZCLADORAS DOBLES SOLDADOS
STRUCTURE, CUVE ET OUVERTURE RENFORCÉE
3 PALES DOUBLES DE MALAXAGE MÉCANO-SOUDÉE
VERSTÄRKTÉ RAHMEN UND TROMMELÖFFNUNG MIT 3
GESCHWEISSTE DOPPEL-MISCHSCHAUFELN
REINFORCED STRUCTURE, DRUM AND OPENING
3 DOUBLE MIXING BLADES

TIMON COM GANCHO DE ENGATE HOMOLOGADO
TIMON CON GANCHO DEL REMOLQUE HOMOLOGADO
TIMON HOMOLOGUÉ DOUBLE POSITION
HOMOLOGIERTE ANKUPPLUNG
TYPE APPROVED TOW HOOK

2 ROLAMENTOS CÔNICOS
3 ROLAMENTOS TRANSMISSÃO
2 RODAMIENTOS CÔNICOS
3 RODAMIENTOS TRANSMISION
2 ROULEMENTS CONIQUES SUR L'AXE DE CUVE
ET 3 ROULEMENTS SUR L'AXE DU PIGNON
2 KONISCHE LAGER
3 GETRIEBELAGER
2 CONICAL BEARINGS
3 TRANSMISSION BEARINGS

PROTEÇÃO DE CREMALHEIRA OPCIONAL
PROTECCIÓN DE RACK OPCIONAL
PROTECTION DE LA COURONNE EN OPTION
ZAHNRADSCHUTZ ALS OPTION
OPTIONAL GEAR RING PROTECTION



Pés galvanizados

Pies galvanizados

Pieds galva

Galvanisiertefüße

Galvanized feet

500 RLAT EVO

400 RLAT EVO

280 RLAT EVO

	500 RLAT EVO	400 RLAT EVO	280 RLAT EVO
DOSAGEM CAPACIDAD DOSAGE DOSIERUNG DOSAGE	2 x 50kg + 35Kg	35 Kg + 35 Kg	25 + 35 Kg
SEM MOTOR SIN MOTOR SANS MOTEUR OHNE MOTOR WITHOUT ENGINE	285 Kg	251 Kg	189 Kg
PRODUÇÃO HORÁRIA PRODUÇÃO HORÁRIA PRODUCTION HORAIRE STUNDENPRODUKTION PRODUCTION PER HOUR	3,30 m3/h	2,60 m3/h	2,00 m3/h
TOTAL BALDE MÁX. DEL BOMBO CAPACITÉ DE LA CUVE TROMMELINHALT DRUM CAPACITY	460 L	360 L	260 L
MÁX. DE MISTURA MÁX. DE MEZCLA MAX DE MALAXAGE MISCHLEISTUNG MAX. MIXING	430 L	330 L	230 L
DIMENSÕES DIMENSIONES DIMENSIONS DIMENSIONS	1950 x 1230 x 1650 mm	1800 x 1100 x 1600 mm	1700 x 960 x 1520 mm

OPÇÃO OPCIÓN OPTION OPTION OPTION



CONTA HORAS
CONTA HORAS
COMPTÉUR D'HEURES
STUNDENZÄHLER
HOUR METER



ARRANQUE ELÉCTRICO
ARRANQUE ELÉCTRICO
DÉMARRAGE ÉLECTRIQUE
ELEKTRO STARTER
ELECTRIC STARTER



SIRL MOTORS 3,0 hp
500 RLAT EVO

SIRL MOTORS 2,0 hp
400 RLAT EVO 280 RLAT EVO

ELÉTRICO ELECTRICO ÉLECTRIQUE ELEKTRO ELECTRIC



SIRL MOTORS KM173F
3,8 hp

KOHLER 15LD 225
4,5 hp

DIESEL

KOHLER KD15-350
7,0 hp



HONDA GX 160
5,5 hp

BRIGGS & STRATTON CR 950
6,5hp



Robin SUBARU EX 17
5,7 hp

GASOLINA GASOLINA ESSENCE BENZIN PETROL